



Husqvarna®



**LOAD INDICATOR**

The LED indicator shows the load of the machine, allowing the operator to always drill at maximum pressure, for best performance.



**WATERCOOLED 3 SPEED GEARBOX**

Watercooled 3 speed gearbox for optimal drilling performance and longer service intervals.

Distributed By:



[www.onesourcerental.com](http://www.onesourcerental.com)

## Husqvarna DMS 280

*The DMS 280 is a complete core drilling system for a variety of drilling applications. The system drills reinforced concrete, bricks, and other building material up to 16" in diameter. The stand is tiltable for angle drilling, and features a convenient carry handle. Bit sold separately.*

## Features Husqvarna DMS 280

- Two-speed carriage gear box lets you choose crank speed for optimal performance, depending on application.
- Maximum 16" (extra spacer required) bit capacity with adapter.
- Plastic strips protect the aluminum column.
- V-groove roller carriage for accurate alignment requiring minimal adjustment.
- The drill stand is tiltable and the back support has a rigid locking system, for reliable and stable angle drilling.
- ATS-V model includes vacuum plate.

TECHNICAL SPECIFICATION	
Input power	2300 W
Voltage	115 V
Rated current, A	20 A
Rated output, W	1500/0 W
Max drill bit diameter	16 inch
Travel length	25.5/0 inch
Drill connection	1" 1/4
Column size	diameter: 0"; height: 42 "
Column height	1067 mm
Total weight	39 kg
Sound level	99 dB(A)
Sound pressure	106 dB(A)

Distributed By:



[www.onesourcerental.com](http://www.onesourcerental.com)

